SINCE 1975

Dimple

AIR COMPRESSOR

7rusted Brand Over Four Decades



Dimple

DCTC 300 (3 HP)

SALIENT FEATURES:

- » 1 HP to 60 HP
- » Easy Installation & Maintenance
- » More Free Air Delivery (cfm)
- » Industrial Quality Design
- » Low Oil Consumption
- » Low Noise & Power, More Air
- » High Operating Efficiency
- » Competitive Prices











RECIPROCATING AIR COMPRESSORS





DCSC 10 (1HP)

DCSC 20 (2 HP)

DOUBLE STAGE INDUSTRIAL AIR COMPRESSORS

MODEL	НР	NO. OF CYLINDER	TANK CAPACITY IN LTRS	DISPLACEMENT (FAD)			WORKING PRESSURE	
				CFM	LPM	M3/HR	KG/CM ²	PSI
DCTC 200	2	2	200	5.4	170	10.2	12	175
DCTC 300	3	2	200	10.5	245	14.7	12	175
DCTC 500	5	2	250	17.5	390	23.4	12	175
DCTC 600	7.5	2	250	25.0	493	29.6	12	175
DCTC 1000	10	3	500	35.0	834	50.2	12	175
DCTC 1500	15	3	500	54.0	1226	73.6	12	175

SINGLE STAGE INDUSTRIAL AIR COMPRESSORS

MODEL	HP	CYLINDER	TANK CAPACITY	CFM	KG/CM ²	PSI
DCSC 5	0.5	1	150	2.10	12	10
DCSC 10	1	1	200	4.3	12	10
DCSC 20	2	1	300	6.1	12	10

Special Features

Piston & Rings: Low expansion aluminum alloy piston with international standard piston rings for positive sealing are elevated temperatures.

Crank Case & End Covers: high quality graded cast iron. Cylinder: Special cast iron, deep finned for quick heat dissipation.

Finger Valves 7 Disc Valves L Special hardened, ground / lapped stainless steel for longer durability & less wear and tear.

Air Receivers: All air receivers are hydro-pressure tested and all compressors are tested for specified cycles in final assembled condition.

Fan: Aero dynamically designed fan with large blades for higher air flow.

Crank Shaft Assembly: Made of carbon steel dynamically balanced with roller bearings for connecting rod big end and deep groved ball bearings for journals assembled true Y & X axis.

Inter/After Cooler: Deep finned a luminum alloy special designed to keep the temperature low and to minimise the formation of carbon.

Standard Accessories (in our scope of supply)

- » Auto pressure control switch.
- » Pressure gauge, Safety valves, air outlet ball valve and non-return valves, Motor Pulley.
- » V-Belts supplied with motor only.
- » All the above models are stationary models. Tank mounted mono block compressors, Mobile units, base mounted units can be made as per customers requirements.
- » Sophisticated manufacturing facility with R&D metrology department a totally integrated, pressurized machine shop.
- » Success its sales spread all over India.
- » Is one of the best equipped organisation in India.





J.S. KALSI INDUSTRIES

(An ISO 9001: 2015 CERTIFIED CO.)

56-B, industrial Area-A Extension, Near Water Tank, Ludhiana-3, Punjab, INDIA M. +91-98729-86925, 85925, 84925 E-mail: jskalsiinds@yahoo.com website: www.dimpleaircompressors.com